



















Size range is a guide only Ultimate Windows manufacture all windows to custom sizes

STANDARD INCLUSIONS

- · Quality hardware.
- Key lock or turn snib cylinder for extra security.
- · High quality rollers for smooth sliding.
- Ultimate's custom designed flydoors.
- Advanced multipoint locking system.
- All doors are double glazed with standard Insulated Glass Units 24mm with argon gas fill.
- All doors glazed on site by our expert tradesmen.
- · High performance dual seals.

PERFORMANCE

- 5 chambered system for superior thermal performance.
- All round steel reinforced for structural strength.
- Doors have been tested to Australian Standard AS 2047.
- Doors can be manufactured to comply with AS 3959 up to and including BAL 40 (Stacker Doors only achieve BAL 29).
- Doors achieve a Water Penetration Resistance of 200pa.

OTHER OPTIONS

- Low E Insulated Glass Units can be supplied in place of clear.
- · Warm edge spacer.

· Maximum door width 1500mm (4 panel door unit maximum

- Higher wind ratings than N3 can be achieved please specify if a higher rating is required.
- Tailored glass solutions to satisfy your needs, upgrades for safety, security, thermal performance, acoustic performance, privacy, aesthetics, comfort.

OPTIONAL CONFIGURATIONS

- · Doors can be on left- or right-hand side or in centre.
- · Bi parting double sliding doors in centre available.
- 3 and 6 Panel stacking doors available.
- · Corner units available.
- Drawings shown are viewed from inside.
 Sizes can be outside of what is shown in this chart.



ACCESSORIES

Door handles available in white, silver and black, special colours can be requested.



OPENING SIZE LIMITATIONS

· Maximum door height 2700mm.

• Maximum door size 3.6m2.

width 1400mm).

FRAME SIZE GUIDE All windows are manufactured to your specified sizes.



3 PANEL STACKER SLIDING DOORS



6 PANEL STACKER SLIDING DOORS



OPTIONAL CONFIGURATIONS

Stacker door configuration

Sliding door configuration

